

PIRANHA OFFROAD PRODUCTS

BTNP300

'Piranha Off Road products are not associated in any way with Nissan Motor Co. (Australia) Pty Ltd or any of its related companies'

To Suit NISSAN Navara NP300 (D23) 2015 For Vehicles with rear Coil Suspension Only

Part Number	BTNP300
Approx Fitting Time	.5 Hours
Max Battery Size	N/A
Recommended Type	Optima D31A
Tray Location	UnderBody



1. Use a workshop hoist or axle stands to put rear suspension into full droop.
2. Remove 3 bolts holding hand brake mounting brackets and 2 bolts holding exhaust hanger, from cross- member above tail-shaft.
3. Manipulate tray into position, from between exhaust and D/S/R wheel. Move tray towards fuel tank, align plates on front edge to encapsulate cross-member, then slide back towards D/S.
4. Place U-bolts and saddles onto tubular cross-member at rear of tray – loosely assemble U-bolts. Re-fit 2 original bolts into exhaust hanger, through tray plate and tighten. Tighten U-bolts.
5. Reinstall 3 original bolts holding hand brake mounting brackets and tighten.
6. Bolt heat shield to tray.
7. Install battery – Battery is heavy!. Seek assistance to manoeuvre battery into tray (from between rear of fuel tank and diff), with positive terminal towards the front. Use Hold Down Top Mount plate and M8 bolt to secure battery.
8. Fit DBAOC in fuse box beside main battery – original fuse is 10Amp, marked "ALT". Not required with DC/DC

PARTS INCLUDED WITH TRAY

- 1 x Hold Down Top Mount
- 1 x M8 Bolt for hold down top mount
- 2 x U-bolt Assemblies
- 1 x Heat Shield
- 6 x M8 short bolts for heat shield

RECOMMENDED ISOLATOR

DC / DC