






IDENTIFICATION CHART



VA crossbar



EURO crossbar



HD crossbar

Vehicle	Date	Crossbar	FRONT CROSSBAR					REAR CROSSBAR						
			Front Right Pad/ Clamp	Front Left Pad/ Clamp	Measurement strip length per side	Measurement strip length per side	Measurement Distance (x)	Foot plate arrow direction	Rear Right Pad/ Clamp	Rear Left Pad/ Clamp	Measurement strip length per side	Measurement strip length per side	Measurement Distance (x)	Foot plate arrow direction
Toyota Hilux Double Cab	10/15-	1260mm	M698 SUB0641	M697 SUB0641	150mm	37mm	948mm / 37,21/64"	OUT	M700 SUB0641	M699 SUB0641	146mm	33mm	940mm / 37,1/64"	OUT
			Pad Arrow FORWARD						Pad Arrow FORWARD					
Toyota Hilux Revo Double Cab	07/15-	1260mm	M698 SUB0641	M697 SUB0641	150mm	37mm	948mm / 37,21/64"	OUT	M700 SUB0641	M699 SUB0641	146mm	33mm	940mm / 37,1/64"	OUT
			Pad Arrow FORWARD						Pad Arrow FORWARD					



DK430, DK430F, DK430R Rhino-Rack VA, Euro & HD crossbar instruction


CONTROLLED

Measurement A: CENTRE of door jamb to CENTRE arrow of leg foot plate.


Measurement B: CENTRE of Front leg foot plate arrow to CENTRE of Rear leg foot plate arrow.

Carrying capacity: Roof rack is rated to 75kg. Please refer to manufacturers handbook for your vehicles maximum roof load capacity. Always use the lower of the two figures.

If your vehicle is not listed on this fitting instruction please refer to your countries Rhino-Rack web site for the latest information.



Note: Clamps, when placed in position untightened, do not follow the contour of the roof. This will correct as the clamp is tightened.



VEHICLE	Date	Measurement A	Measurement B	Measurement C	Load Rating (includes racks 5kg/ 11lbs)
Toyota Hilux Double Cab	10/2015 -	256mm / 10,5/64"	737mm / 29,1/64"	481mm/ 18,15/16"	75kg / 165lbs
Toyota Hilux Revo Double Cab	7/2015 -	256mm / 10,5/64"	737mm / 29,1/64"	481mm/ 18,15/16"	75kg / 165lbs